

CAT. N° 4 199 49



## MCB RX<sup>3</sup> 4500 - 1P+N 230 V~ - 16 A - C CURVE - NEUTRAL ON LEFT-HAND SIDE

Pack (number of units)	10
Volume (dm <sup>3</sup> )	1,633
Weight (g)	1 062,00

### Product characteristics

#### Single pole + neutral 230 V~ neutral on left-hand side

- C curve
- Nominal rating I<sub>n</sub> : 16 A
- Number of modules : 1

### General characteristics

#### MCBs RX<sup>3</sup> 4500 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
  - 4500 - IEC 60898-1 - 230/400 V~
  - 4.5 kA - IEC 60947-2 - 230/400 V~
  - 6000 - IEC 60898-1 - 127/220 V~
  - 6 kA - IEC 60947-2 - 127/220 V~

### Documentation



#### Catalogue pages & additional information

- [Description page \(p.051\)](#)
- [Dimensions of din-rail equipment](#)



#### Agreements & certificates of conformity

- [QC / CB-670457](#)



#### Installation & technical data

- [F02068EN-00](#)



#### Environmental product profile

- [LGRP-00358-V02](#)